



New Orleans: (504) 733-1808
Houston: (713) 671-6061
New York: (914) 729-7807
California: (714) 994-3070

GeneralWorkProducts.com
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

GWP 6.5mm Black Polypropylene Danline Rope (3-Strand)

Part #: RP-I3DLBK-06MX04000

GWP 3-Strand Polypropylene Danline Rope, commonly referred to as "Hoop rope," provides exceptional durability and reliability for demanding industrial applications. Engineered from premium polypropylene resin, this lightweight, floating rope features strong UV resistance to withstand prolonged outdoor exposure without degrading.

FEATURES

- Strong UV Resistance for extended outdoor lifespan.
- Constructed from high-quality Polypropylene Resin.
- Classic 3-Strand design for excellent knot retention and splicing.
- High strength-to-weight ratio with a 6:1 Factor of Safety.



TECHNICAL DATA

Part #	Diameter	Length	Material	Color	Minimum Breaking Load (MBL)	Safety Factor	Testing Standard
RP-I3DLBK-06MX04000	6.5mm	4,000 ft. (per spool/reel)	Polypropylene Resin	Black	1,250 lbs.	6:1	Tested as per ISO 2307:2019

Specifications are subject to change without notice. General Work Products makes no warranties to the use for a specific use or installation of products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability for resulting loss or damage. General Work Products recommends installing the herein specified products in accordance with ANSI A-10-11-1989 and OSHA 1926.502 or all applicable local, state or federal requirements. Correct installation is the sole responsibility of the user/installer.