

PN: H212100014



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808
Fax: (504) 733-2996
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

Harness 5pt., Urethane Coated, Back D-Ring, Grommet Legs, Red Color

Red Urethane Coated Harness 5pt., Pass Thru Chest, Grommet Legs, Back D-Ring, No SRL Loop, Rated 420 lbs., Meets or Exceeds ANSI Z359.11-2014, A10.32-2012, Sizes: Universal, 2XL and 3XL.



- DESIGN:**
- One dorsal attachment D-ring for fall arrest; 5 adjustment points.
 - Adjustable shoulder straps with spring adjust buckles and pass-thru chest buckle
 - Adjustable tongue buckle leg straps.
 - Spark resistant urethane coated torso and leg straps.

WEBBING: Material: Polyester & Urethane | Width: 1.77 in. \pm 0.008 in. (45mm \pm 0.2mm)
Thickness: 0.09 in. \pm 0.003 in. (2.3mm \pm 0.1mm) | Breaking Strength: 6000 lbs.

STITCHING THREAD: Material: High-tenacity polyester | Color: White

METAL COMPONENT: Material: Steel | Finish: Silver or yellow golden galvanized

CONFORMS TO: Meets or Exceeds ANSI Z359.11-2014

CAPACITY: ANSI 310 lbs. & OSHA 420 lbs.

Part #	Size
H212100014	Universal
H212100014.2X	2XL
H212100014.3X	3XL