

PN: H223100521



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808  
Fax: (504) 733-2996  
PalmerSafetyUS.com

## TECHNICAL SPECIFICATIONS

### Harness 5pt., QCB, Padded Back, Back D-ring. Black color

Black Top, 5 point FBH, QCB Chest, All Aluminum Hardware, Reflective Padded Back Sewn In, Padded Grommet Legs, and Dorsal D-ring with SRL Back Plate. Universal size. Meets or Exceeds ANSI Z359.11-2014 A10.32-2013.



**USER CAPACITY:** 130 - 310 lbs.

• Aluminum Quick release buckles for adjustment at shoulder, chest & leg straps. Min. 4000 lbs. strength

**DESIGN:** • Aluminum D-ring at dorsal for fall arrest, Min. 5000 lbs. strength  
• Shoulder/Back pad (reflective) & Leg pad  
• Two lanyard keepers have been incorporated to store unused leg of the lanyard

**WEBBING:** Material: Polyester | Width: 1.73 in.  $\pm$  0.008 in. (44mm  $\pm$  0.2mm)  
Breaking Strength: 6500 lbs. (Min.)

**STITCHING THREAD:** Material: High Tenacity Polyester

**METAL COMPONENT:** Material: Aluminum

**CONFORMS TO:** Meets or Exceeds ANSI Z359.11-2014