

PN: H223111621

TECHNICAL SPECIFICATIONS

Akula™ Series Harness 5pt., Padded Back/Legs, QCB, SRL Back Plate, Positioning Belt with Side D-Rings, Black

3 D-ring harness with 5 points of easy adjustability, quick connect chest and leg buckles with roller cam torso, sewn-in back and leg moisture wicking padding, form-fit positioning construction belt, built-in srl back plate tunnel for personal self-retracting lifeline, heavy duty tag and impact indicators. Meets or exceeds the performance standards of ANSI Z359.11-2021 and A10.32-2012.



AKULA
HARNESS SERIES



MOISTURE
WICKING
PADDING



USER CAPACITY: 130 - 420 lbs.

- DESIGN:**
- Back dorsal D-Ring for fall arrest
 - SRL back plate tunnel for personal self-retracting device
 - Work positioning side (hip) D-rings
 - Quick connect chest and leg buckles with roller cam torso
 - Breakaway lanyard keepers
 - Built-in construction belt

WEBBING: Material: Polyester | Width: 1.73 in. (44mm)
Breaking Strength: 5000 lbs. (Min.)

**STITCHING
THREAD:** Material: High Tenacity Polyester

**METAL
COMPONENT:** Material: Aluminum | Finish: Powder Coated

CONFORMS TO: Meets or exceeds ANSI Z359.11-2021

WEIGHT: 5.89 lbs.

Part #	Size
H223111621.MD	Medium
H223111621.LG	Large
H223111621.XL	X-Large