

PN: H22312162



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808  
Fax: (504) 733-2996  
PalmerSafetyUS.com

## TECHNICAL SPECIFICATIONS

### Akula™ Series Harness 5pt., Padded Back/Legs, QCB, Positioning Belt Side D-Rings, Back and Dual Front D-Rings, Black



**AKULA**  
HARNESS SERIES

Black top, black padding, 5 point FBH, QCB all aluminum hardware, padded back sewn in, padded legs sewn in. Positioning belt black. 1 Back D-ring, 2 Side D-rings, 2 Front D-rings. SRL back plate. Meets or exceeds ANSI Z359.11-2021. A10.32-2012.



MOISTURE WICKING PADDING



**USER CAPACITY:** 130 - 420 lbs.

**DESIGN:**

- One (1) dorsal attachment D-ring for fall arrest; one (1) front D-ring for climbing purpose; one (1) ventral D-ring for rope access purpose
- Equipped with work positioning belt with two (2) side D-rings for work positioning
- Adjustable shoulder straps for easy adjustment and snug fitting
- Adjustable H-style leg straps for snug fitting
- One (1) lanyard keeper has been incorporated to store unused leg of the lanyard

**WEBBING:** Material: Polyester | Width: 1.73 in. | Breaking Strength: 5000 lbs.

**STITCHING THREAD:** Material: High-tenacity polyester

**METAL COMPONENT:** Material: All Black Aluminum Hardware

**CONFORMS TO:** Meets or exceeds ANSI Z359.11-2021

**WEIGHT:** 5.82 lbs.

Part #	Size
H22312162.S/M	Small - Medium
H22312162.L/XL	Large - X-Large