

TECHNICALSPECIFICATIONS

G-Series 5pt. Harness, QCB, Padded Back and Legs, Back D-Ring, Front D-Ring, Side D-Rings with Positioning Belt, Black Color.

4 D-ring harness with 5 points of easy adjustability, quick connect chest and padded leg buckles with roller cam torso, sewn-in back and leg moisture wicking padding, form-fit positioning construction belt, built-in srl back plate tunnel for personal self-retracting lifeline, EZ park lanyard keepers, built-in trauma relief straps, heavy duty tag and impact indicators. Meets or exceeds the performance standards of ANSI Z359.11-2021.



USER CAPACITY: 130 - 420 lbs.

Back and front dorsal D-Rings for fall arrest

SRL back plate tunnel for personal self-retracting device

· Work positioning side (hip) D-rings

DESIGN: • Quick connect chest and leg buckles with roller cam torso

• EZ park lanyard keepers

· Built-in Trauma Releif Straps

• Built-in construction belt

WEBBING: Material: Polyester | Width: 1.73 in. ± 0.008 in. (44mm ± 0.2mm)

Breaking Strength: 5000 lbs. (Min.)

Part # Size **STITCHING** Material: High Tenacity Polyester HGSERIES03.SM Small THREAD: HGSERIES03.MD Medium **METAL** Material: Aluminum | Finish: Powder Coated HGSERIES03.LG Large **COMPONENT:** HGSERIES03.XL X-Large CONFORMS TO: Meets or Exceeds ANSI Z359.11-2021 HGSERIES03.2XL 2X-Large