

TECHNICAL SPECIFICATIONS

Metal Roof D-Ring Swivel Anchor

Palmer Safety's ANCHORDRINGSW Metal Roof Swivel Anchor is a versatile fall protection solution for metal roofs. Its robust construction provides a secure anchor point for up to 5,000 lbs, while the swivel design allows for unrestricted movement and easy positioning. Ideal for both temporary and permanent applications, this anchor is a must-have for anyone working on metal roofs.

- **Versatile Design:** Fits R-panel and standing seam roofs, connecting directly to the structural below.
- **360° Swivel and 180° D-Ring Flip:** Ensures the anchor is always positioned correctly for maximum safety.
- **High Working Load:** Supports up to 5,000 lbs for secure anchorage.
- **Durable Construction:** Designed for long-lasting performance on metal roofs 22 gauge or thicker.
- **Easy Installation:** Includes self-drilling fasteners for quick and efficient setup.
- **Removable and Reusable:** Can be easily repositioned as needed for ongoing projects.



CAPACITY: Maximum 1 connection per anchor
 Worker Weight Range: 130 – 310 lbs. including all tools and equipment

DESIGN:

- Dimensions: 4" x 8"
- Weight: 3 lbs.

MATERIAL:

- Durable steel construction
- Drop forged D-ring
- Zinc Electroplate finish

MINIMUM BREAKING STRENGTH: 5000 lbs.; 3600 lb max. load

CONFORM TO NORM: Meets or Exceeds all applicable OSHA & ANSI requirements for anchorage devices